


### Product Group MFCB

Articulated machine feet made of glass fibre reinforced polyamide with galvanized steel thread and antislip pad (A)




#### Standard Colours

- black

#### Material

- Thread: zinc-plated steel
- Base: glass fibre reinforced polyamide (PA-GF)
- Antislip pad: NBR 70 Shore



#### Product information

- There are two prepared screw-on holes (closed).
- The machine foot can compensate for uneven floors up to 30°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Packaging industry, conveyor systems, automation industry, office desks, aluminium profiles

#### Product options on inquiry

- Delivery with additional steel nut possible.

| A  | D   | d    | F max. | H  | H1 | M   | WAF | 50 | 100 | 150 | 200 | 250 |
|----|-----|------|--------|----|----|-----|-----|----|-----|-----|-----|-----|
| mm | mm  | mm   | kg     | mm | mm |     | mm  | mm | mm  | mm  | mm  | mm  |
| 54 | 83  | 8,5  | 1000   | 18 | 30 | M10 | 7   | x  | x   | x   |     |     |
| 54 | 83  | 8,5  | 1300   | 18 | 30 | M12 | 9   | x  | x   | x   |     |     |
| 54 | 83  | 8,5  | 1600   | 18 | 30 | M16 | 13  |    | x   | x   | x   |     |
| 54 | 83  | 8,5  | 1800   | 18 | 32 | M20 | 17  |    | x   | x   | x   | x   |
| 73 | 103 | 12,5 | 1800   | 20 | 32 | M16 | 13  |    | x   | x   | x   |     |
| 73 | 103 | 12,5 | 2000   | 20 | 32 | M20 | 17  |    | x   | x   | x   | x   |
| 73 | 103 | 12,5 | 2500   | 20 | 32 | M24 | 20  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 1800   | 22 | 34 | M16 | 13  |    | x   | x   | x   |     |
| 87 | 123 | 12,5 | 2000   | 22 | 36 | M20 | 17  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 2500   | 22 | 36 | M24 | 20  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 2500   | 22 | 36 | M30 | 20  |    | x   |     |     |     |
| 87 | 123 | 12,5 | 2500   | 22 | 36 | M30 | 26  |    |     | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ---> MFCB 83 M16x 100 (A)