


### Product Group MFCSW

Articulated machine feet made of glass fibre reinforced polyamide with stainless steel thread, cover between foot/thread and antislip pad (A)




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Base: glass fibre reinforced polyamide (PA-GF)
- Antislip pad: NBR 70 Shore



#### Product information

- There are two prepared screw-on holes (closed).
- The machine foot can compensate for slopes of up to 16° on floors and equipment.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Packaging industry, conveyor systems, automation industry, office desks, aluminium profiles
- Food industry

#### Product options on inquiry

- Delivery with additional steel nut possible.
- Thread made of stainless steel AISI 316 (A4)

| A  | D   | d    | F max. | H  | H1 | M   | WAF | 50 | 100 | 150 | 200 | 250 |
|----|-----|------|--------|----|----|-----|-----|----|-----|-----|-----|-----|
| mm | mm  | mm   | kg     | mm | mm |     | mm  | mm | mm  | mm  | mm  | mm  |
| 54 | 83  | 8,5  | 1400   | 25 | 35 | M12 | 9   | x  | x   | x   |     |     |
| 54 | 83  | 8,5  | 1400   | 25 | 35 | M16 | 13  |    | x   |     |     |     |
| 54 | 83  | 8,5  | 2000   | 25 | 35 | M16 | 13  |    | x   | x   | x   |     |
| 54 | 83  | 8,5  | 2000   | 25 | 37 | M20 | 17  |    | x   | x   | x   | x   |
| 54 | 83  | 8,5  | 2000   | 25 | 37 | M24 | 20  |    | x   | x   | x   | x   |
| 73 | 103 | 12,5 | 3000   | 26 | 36 | M16 | 13  |    | x   | x   | x   |     |
| 73 | 103 | 12,5 | 3000   | 26 | 36 | M20 | 17  |    | x   | x   | x   | x   |
| 73 | 103 | 12,5 | 3000   | 26 | 36 | M24 | 20  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 3500   | 29 | 39 | M16 | 13  |    | x   | x   | x   |     |
| 87 | 123 | 12,5 | 3500   | 29 | 41 | M20 | 17  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 3500   | 29 | 41 | M24 | 20  |    | x   | x   | x   | x   |
| 87 | 123 | 12,5 | 3500   | 29 | 41 | M30 | 26  |    | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ---> MFCSW 83 M16x 100 (A)