


Product Group MFHXB

Machine feet made of stainless steel with rubber base, fixing plate and concealed transition from foot to thread




Standard Colours

- black

Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The machine base is a hygienically well thought-out design in which the transition from the base plate to the threaded spindle is concealed.
- The machine foot can be fixed to the floor.
- The cast-in mounting plate ensures that the foot dampens vibrations even after it has been fixed to the floor.
- The embedded rubber meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

D	B	d	F max.	H	M	WAF	49	70	97	139	172	223	305
mm	mm	mm	kg	mm		mm	mm	mm	mm	mm	mm	mm	mm
65	46,8	15	900	34	M12	10	x	x	x	x			
65	46,8	15	900	34	M16	13		x	x	x	x	x	
65	46,8	15	900	34	M20	17		x	x	x	x	x	x
65	46,8	15	900	34	M24	19		x	x	x	x	x	x
65	46,8	15	710	34	M12	10					x		
65	46,8	15	420	34	M12	10						x	
65	46,8	15	220	34	M12	10							x
65	46,8	15	790	34	M16	13							x
80	53,2	15	1500	39	M12	10		x	x				
80	53,2	15	1500	39	M16	13		x	x	x	x		
80	53,2	15	1500	39	M20	17		x	x	x	x	x	x
80	53,2	15	1500	39	M24	19		x	x	x	x	x	x
80	53,2	15	1500	33	M30	24		x	x	x	x	x	x
80	53,2	15	1090	39	M12	10				x			
80	53,2	15	710	39	M12	10					x		
80	53,2	15	420	39	M12	10						x	
80	53,2	15	1480	39	M16	13						x	
80	53,2	15	790	39	M16	13							x
105	70	15	2200	39	M16	13		x	x	x	x		



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

D	B	d	F max.	H	M	WAF	49	70	97	139	172	223	305
mm	mm	mm	kg	mm		mm	mm	mm	mm	mm	mm	mm	mm
105	70	15	2200	39	M20	17		x	x	x	x	x	
105	70	15	2200	39	M24	19		x	x	x	x	x	x
105	70	15	2200	34	M30	24		x	x	x	x	x	x
105	70	15	2200	34	M36	30			x	x	x	x	x
105	70	15	1480	39	M16	13						x	
105	70	15	790	39	M16	13							x
105	70	15	1940	39	M20	17							x

Ordering example

• Group + D + M + Thread Length ---> MFHXB 105 M16 x 100