


Product Group OVL/GD

Lamella plugs made of PE for flat oval tubes with convex lid




Standard Colours

- black RAL 9005

Material

- Polyethylene (PE)



Product information

- The plugs are intended for use in pipes or equivalent bores with free passage corresponding to the clear nominal width of at least shaft length.
- For technical production reasons, a residual sprue may exceed the shaft length.
- Material and design of shafts guaranteed stop against drop out and easy assembling.
- For use as a glides (conditional shear strength) and to attain an easy assembling in tubes with larger wall thickness, it is recommended to chamfer the inside diameter of the pipe (approx. $0.3 - 0.5 \times 60^\circ$).
- Depending on the selected article, the surface finish can vary between polished and eroded.
- The ribs are circularly closed or interrupted.
- They are not suitable for sealing against fluids.
- The number of slats per plug varies between 2-4 slats.
- GD = cambered top (like series SRL)
- Your searched size / design is not included? - Please ask our sales team!
- As a rule, odd outside pipe diameters rounded to 1/10 mm (as part of the article or order number) indicate that these sizes originate from or are common in the Imperial system.

Product options on inquiry

- Special colours (colours, minimum quantities, set-up costs, pricing and surcharges)
- With your engraved company logo (tooling costs, minimum quantities, set-up costs)
- With your tampon printed company logo (set-up costs, minimum quantities, printing costs)
- Most plugs can also be made of suitable harder TPE's (TPE= thermoplastic elastomer --> extended range of operating temperature, noise absorbing, non-skid).

Order Number	A	B	H	H1	L	t
	mm	mm	mm	mm	mm	mm
OVL 20x10x0,75-2 GD	20	10	3	3	11,5	0,75-2
OVL 25x10x0,8-2 GD	25	10	3	3	11,5	0,8-2
OVL 30x10x0,8-2 GD	30	10	3	3	11,5	0,8-2
OVL 30x15x1,5-2 GD	30	15	4	3	16	1,5-2
OVL 35x15x0,8-2,5 GD	35	15	4	3	11,5	0,8-2,5
OVL 35x20x1-3 GD	35	20	5	3	11,5	1-3
OVL 38x20x1,5 GD / 20	38	20	5	3	20	1,5
OVL 38x20x1-3 GD	38	20	5	3	11,5	1-3
OVL 40x20x0,8-2,5 GD	40	20	5	3	11,5	0,8-2,5
OVL 48x20x1-2,5 GD	48	20	5	3	11,5	1-2,5



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

Order Number	A	B	H	H1	L	t
	mm	mm	mm	mm	mm	mm
OVL 50x20x1-3 GD	50	20	5	3	11,5	1-3
OVL 50x25x1-3 GD	50	25	3	3	11,5	1-3
OVL 50x30x1-3 GD	50	30	5	3	11,5	1-3
OVL 60x20x0,8-2,5 GD	60	20	5	3	11,5	0,8-2,5
OVL 60x30x1,5-2 GD	60	30	8	3,5	13,5	1,5-2
OVL 70x40x1-3 GD	70	40	5	3	14,5	1-3
OVL 80x25x1,2-2,5 GD	80	25	5	3	14,5	1,2-2,5