


### Product Group MFMB

Machine feet made of stainless steel with rubber base and one fixing strap




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The machine foot can be fixed to the floor.
- The cast-in mounting plate ensures that the foot dampens vibrations even after it has been fixed to the floor.
- The rounded and hygienic design of this type enables easy and quick cleaning.
- The embedded rubber meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 5°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

D	A	B	d	F max.	H	M	WAF	50	70	100	150	180	230	310
mm	mm	mm	mm	kg	mm		mm	mm	mm	mm	mm	mm	mm	mm
75	67	52	14,85	800	22	M10	8	x	x	x	x	x	x	
75	67	52	14,85	800	22	M12	10	x	x	x	x	x	x	
75	67	52	14,85	800	22	M16	13		x	x	x	x	x	x
75	67	52	14,85	800	22	M20	15		x	x	x	x	x	x
75	67	52	14,85	800	22	M24	19		x	x	x	x	x	x
75	67	52	14,85	800	22	M30	24		x	x	x	x	x	x
100	82	67	14,85	1000	32	M12	10	x	x	x	x	x	x	
100	82	67	14,85	1000	32	M16	13		x	x	x	x	x	x
100	82	67	14,85	1000	32	M20	15		x	x	x	x	x	x
100	82	67	14,85	1000	32	M24	19		x	x	x	x	x	x
100	82	67	14,85	1000	32	M30	24		x	x	x	x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> MFMB 75 M16 x 100