


Product Group MFMB

Machine feet made of stainless steel with rubber base and one fixing strap




Standard Colours

- black

Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The machine foot can be fixed to the floor.
- The cast-in mounting plate ensures that the foot dampens vibrations even after it has been fixed to the floor.
- The rounded and hygienic design of this type enables easy and quick cleaning.
- The embedded rubber meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 5°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D | A | B | d | F max. | H | M | WAF | 50 | 70 | 100 | 150 | 180 | 230 | 310 |
|-----|----|----|-------|--------|----|-----|-----|----|----|-----|-----|-----|-----|-----|
| mm | mm | mm | mm | kg | mm | | mm | mm | mm | mm | mm | mm | mm | mm |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M10 | 8 | x | x | x | x | x | x | |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M12 | 10 | x | x | x | x | x | x | |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M16 | 13 | | x | x | x | x | x | x |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M20 | 15 | | x | x | x | x | x | x |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M24 | 19 | | x | x | x | x | x | x |
| 75 | 67 | 52 | 14,85 | 800 | 22 | M30 | 24 | | x | x | x | x | x | x |
| 100 | 82 | 67 | 14,85 | 1000 | 32 | M12 | 10 | x | x | x | x | x | x | |
| 100 | 82 | 67 | 14,85 | 1000 | 32 | M16 | 13 | | x | x | x | x | x | x |
| 100 | 82 | 67 | 14,85 | 1000 | 32 | M20 | 15 | | x | x | x | x | x | x |
| 100 | 82 | 67 | 14,85 | 1000 | 32 | M24 | 19 | | x | x | x | x | x | x |
| 100 | 82 | 67 | 14,85 | 1000 | 32 | M30 | 24 | | x | x | x | x | x | x |

Ordering example

- Group + D + M + Thread Length ---> MFMB 75 M16 x 100