


### Product Group MFK

Machine feet made of stainless steel with rubber base to cope slopes on the floor and equipment




#### Standard Colours

- white

#### Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The rounded design of this type makes cleaning easy.
- The rubber pressed into the foot plate meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 20°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

D	F max.	H	M	WAF	50	70	100	150	180	230	310
mm	kg	mm		mm	mm	mm	mm	mm	mm	mm	mm
75	800	21	M12	10	x	x	x	x	x		
75	800	21	M16	13		x	x	x	x	x	x
75	800	21	M20	15		x	x	x	x	x	x
75	800	21	M24	19		x	x	x	x	x	x
75	800	21	M30	24					x	x	
100	2000	36	M12	10	x	x	x	x	x		
100	2000	36	M16	13		x	x	x	x	x	x
100	2000	36	M20	15		x	x	x	x	x	x
100	2000	36	M24	19		x	x	x	x	x	x
100	2000	36	M30	24		x	x	x	x	x	x
125	3000	40	M12	10	x	x	x	x	x		
125	3000	40	M16	13		x	x	x	x	x	x
125	3000	40	M20	15		x	x	x	x	x	x
125	3000	40	M24	19		x	x	x	x	x	x
125	3000	40	M30	24		x	x	x	x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> MFK 100 M16 x 100