


### Product Group MFHP

Adjustable feet made of glass fibre reinforced polyamide with plastic base and stainless steel thread




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Base: glass fibre reinforced polyamide (PA-GF)
- Top cover: Polypropylene carbonate (PPC)



#### Product information

- The machine foot is particularly characterized by its hygienic construction, mounting flexibility and resistance to outer influences.
- From Ø 80 mm the foot can be screwed to the floor - for this purpose there are prepared screw holes (closed) below the clipped-on cover.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

D	H	B	d	F max.	M	WAF	70	100	150	180	230	310
mm	mm	mm	mm	kg		mm	mm	mm	mm	mm	mm	mm
60	31			1200	M12	10	x	x	x	x	x	
60	31			1200	M16	13	x	x	x	x	x	x
60	31			1200	M20	17	x	x	x	x	x	x
60	31			1200	M24	19	x	x	x	x	x	x
80	31	27	9	1200	M12	10	x	x	x	x		
80	31	27	9	1200	M16	13	x	x	x	x	x	
80	31	27	9	1200	M20	17	x	x	x	x	x	
80	31	27	9	1200	M24	19	x	x	x	x	x	
100	37	32	11	2000	M12	10	x	x	x	x		
100	37	32	11	2000	M16	13	x	x	x	x	x	
100	37	32	11	2000	M20	17	x	x	x	x	x	
100	37	32	11	2000	M24	19	x	x	x	x	x	
120	37	40	11	2000	M12	10	x	x	x	x		
120	37	40	11	2000	M16	13	x	x	x	x	x	
120	37	40	11	2000	M20	17	x	x	x	x	x	
120	37	40	11	2000	M24	19	x	x	x	x	x	

#### Ordering example

- Group + D + M + Thread Length ---> MFHP 100 M16 x 100