


### Product Group MFHPR

Adjustable feet made of glass fibre reinforced polyamide with rubber base, stainless steel top cover and stainless steel thread




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Base: glass fibre reinforced polyamide (PA-GF)
- Top cover: AISI 304 (A2)
- Rubber: NBR 80 Shore



#### Product information

- The machine foot is particularly characterized by its hygienic construction, mounting flexibility and resistance to outer influences.
- From Ø 80 mm the foot can be screwed to the floor - for this purpose there are prepared screw holes (closed) below the clipped-on cover.
- The anti-slip rubber is vulcanized into the plastic disc.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D   | H  | B  | d  | F max. | M   | WAF | 70 | 100 | 150 | 180 | 230 | 310 |
|-----|----|----|----|--------|-----|-----|----|-----|-----|-----|-----|-----|
| mm  | mm | mm | mm | kg     |     | mm  | mm | mm  | mm  | mm  | mm  | mm  |
| 80  | 33 | 27 | 9  | 1200   | M12 | 10  | x  | x   | x   | x   | x   |     |
| 80  | 33 | 27 | 9  | 1200   | M16 | 13  | x  | x   | x   | x   | x   | x   |
| 80  | 33 | 27 | 9  | 1200   | M20 | 17  | x  | x   | x   | x   | x   | x   |
| 80  | 33 | 27 | 9  | 1200   | M24 | 19  | x  | x   | x   | x   | x   | x   |
| 100 | 39 | 32 | 11 | 2000   | M12 | 10  | x  | x   | x   | x   | x   |     |
| 100 | 39 | 32 | 11 | 2000   | M16 | 13  | x  | x   | x   | x   | x   | x   |
| 100 | 39 | 32 | 11 | 2000   | M20 | 17  | x  | x   | x   | x   | x   | x   |
| 100 | 39 | 32 | 11 | 2000   | M24 | 19  | x  | x   | x   | x   | x   | x   |
| 120 | 40 | 40 | 11 | 2000   | M12 | 10  | x  | x   | x   | x   | x   |     |
| 120 | 40 | 40 | 11 | 2000   | M16 | 13  | x  | x   | x   | x   | x   | x   |
| 120 | 40 | 40 | 11 | 2000   | M20 | 17  | x  | x   | x   | x   | x   | x   |
| 120 | 40 | 40 | 11 | 2000   | M24 | 19  | x  | x   | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ---> MFHPR 100 M16 x 100