



Product Group MFKG

Machine feet made of stainless steel, optional with antislip pad



Material

- Base body: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The machine foot is suitable for machines that are subject to thermal expansion and contraction (ovens, freezers, ...).
- The solid stainless steel design makes the foot highly resilient. The rounded shape makes cleaning easier.
- The machine foot can compensate for uneven floors up to 8°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The base is optionally available with a non-slip rubber plate that is firmly bonded to the stainless steel plate.
- Please order separately (MFKGxG, x = D)!
- The foot is used in work areas with low stress.

D	H1	H2	F max.	M	WAF						
mm	mm	mm	kg		mm	mm	100	150	180	230	310
90	17	5	6000	M12	10		x	x	x	x	
90	17	5	6000	M16	13		x	x	x	x	
90	17	5	6000	M20	17		x	x	x	x	
90	17	5	6000	M24	19		x	x	x	x	
90											
110	17	5	6000	M16	13		x	x	x	x	
110	17	5	6000	M20	17		x	x	x	x	
110	17	5	6000	M24	19		x	x	x	x	
110	17	5	6000	M30	24		x	x	x	x	
110											
150	17	5	6000	M16	13		x	x	x	x	
150	17	5	6000	M20	17		x	x	x	x	
150	17	5	6000	M24	19		x	x	x	x	
150	17	5	6000	M30	24		x	x	x	x	x
150											
180	17	5	6000	M20	17		x	x	x	x	
180	17	5	6000	M24	19		x	x	x	x	
180	17	5	6000	M30	24		x	x	x	x	
180	17	5	6000	M36	30		x	x	x	x	



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

D	H1	H2	F max.	M	WAF	mm	100	150	180	230	310
mm	mm	mm	kg		mm		mm	mm	mm	mm	mm
180	17	5	6000	M42	36		x	x	x	x	
180											

Ordering example

• Group + D + M + Thread Length ---> MFKG 110 M16 x 100