


### Product Group HOT

Cable ducts, lateral open, made of polyamide 6.6




#### Standard Colours


- black

#### Material

- Polyamide 6.6 (PA 6.6)



Blech, Platte / Sheet, Panel



#### Product information

- Assembly in borings with pre-routed cables
- Assembly of cables with pre-assembled plugs
- Simple, fast and sure
- Free of halogen
- UL and CSA certified (USA)
- 105 °C Max. permissible operating temperature
- Burning behaviour: UL 94V-2

| Order Number | d    | d1   | D    | D1   | H   | L    | t max. |
|--------------|------|------|------|------|-----|------|--------|
|              | mm   | mm   | mm   | mm   | mm  | mm   | mm     |
| HOT 2865     | 9,5  | 6,7  | 10,7 | 9,5  | 1,1 | 10,3 | 3,2    |
| HOT 2867     | 11,1 | 7,9  | 12,3 | 11,3 | 1,6 | 10,3 | 3,2    |
| HOT 2871     | 12,7 | 7,9  | 14,3 | 12,5 | 1,6 | 10,3 | 3,2    |
| HOT 2869     | 14,3 | 9,9  | 16,3 | 14   | 1,6 | 10,3 | 3,2    |
| HOT 2872     | 15,9 | 11,5 | 17,5 | 15,6 | 1,6 | 10,3 | 3,2    |
| HOT 2873     | 19   | 13,9 | 20,2 | 18,7 | 1,6 | 10,3 | 3,2    |
| HOT 2874     | 22,2 | 17,1 | 23,4 | 22   | 1,6 | 10,3 | 3,2    |
| HOT 2878     | 25,4 | 20,2 | 27   | 23,8 | 1,6 | 10,3 | 3,2    |
| HOT 2879     | 27,8 | 22   | 28,6 | 27   | 1,6 | 10,3 | 3,2    |
| HOT 2881     | 31,8 | 26,6 | 34,1 | 31,3 | 1,6 | 10,3 | 3,2    |
| HOT 2882     | 34,9 | 29,8 | 37,3 | 34,6 | 1,6 | 10,3 | 3,2    |
| HOT 2883     | 38,1 | 31,7 | 40,1 | 38,1 | 2   | 10,7 | 3,2    |