


### Product Group IBM

Blind nuts with stop collar made of neoprene





#### Standard Colours




- black

#### Material

- Base body: Neoprene
- Thread: Brass



Blech, Platte / Sheet, Panel



#### Product information

- Vibration damping and vibration-proof
- Suitable for sensitive materials
- No special tools necessary - simple assembly by screw driver
- Suitable for blind holes
- Oil resistant
- Non-corroding neoprene
- Electrical not conducting
- Temperature resistance between  $-40^{\circ}\text{C}$  and  $+90^{\circ}\text{C}$

Order Number	d	D	D1	H	L	M	t
	mm	mm	mm	mm	mm		mm
IBM 3004	8	11,5	7,9	1,6	11,1	M3	0,4-4,0
IBM 4039	8	11,1	7,9	1,3	11,4	M4	0,4-4,0
IBM 4139	8	19,1	7,9	1,5	12,7	M4	0,4-4,4
IBM 5049	9,6	12,7	9,5	0,9	13,1	M5	0,4-4,9
IBM 5058	9,6	19,1	9,5	4,8	15,8	M5	0,8-5,8
IBM 5057	9,6	19,1	9,5	2	15,7	M5	0,8-5,8
IBM 5059	9,6	14,3	9,5	1	15,9	M5	0,9-5,9
IBM 5114	9,6	14	9,5	0,9	20,6	M5	4,0-10,0
IBM 6028	12,8	16	12,7	1,3	14,7	M6	0,4-4,0
IBM 6047	12,8	18,8	12,7	4,8	16,3	M6	0,8-4,8
IBM 6116	12,8	16,1	12,7	1,3	25,4	M6	6,4-11,6
IBM 8047	15,9	22,2	15,8	3,2	15,2	M8	0,4-4,0