


Product Group IBM

Blind nuts with stop collar made of neoprene








Standard Colours

- black

Material

- Base body: Neoprene
- Thread: Brass



Product information

- Vibration damping and vibration-proof
- Suitable for sensitive materials
- No special tools necessary - simple assembly by screw driver
- Suitable for blind holes
- Oil resistant
- Non-corroding neoprene
- Electrical not conducting
- Temperature resistance between -40°C and $+90^{\circ}\text{C}$

| Order Number | d | D | D1 | H | L | M | t |
|--------------|------|------|------|-----|------|----|----------|
| | mm | mm | mm | mm | mm | | mm |
| IBM 3004 | 8 | 11,5 | 7,9 | 1,6 | 11,1 | M3 | 0,4-4,0 |
| IBM 4039 | 8 | 11,1 | 7,9 | 1,3 | 11,4 | M4 | 0,4-4,0 |
| IBM 4139 | 8 | 19,1 | 7,9 | 1,5 | 12,7 | M4 | 0,4-4,4 |
| IBM 5049 | 9,6 | 12,7 | 9,5 | 0,9 | 13,1 | M5 | 0,4-4,9 |
| IBM 5058 | 9,6 | 19,1 | 9,5 | 4,8 | 15,8 | M5 | 0,8-5,8 |
| IBM 5057 | 9,6 | 19,1 | 9,5 | 2 | 15,7 | M5 | 0,8-5,8 |
| IBM 5059 | 9,6 | 14,3 | 9,5 | 1 | 15,9 | M5 | 0,9-5,9 |
| IBM 5114 | 9,6 | 14 | 9,5 | 0,9 | 20,6 | M5 | 4,0-10,0 |
| IBM 6028 | 12,8 | 16 | 12,7 | 1,3 | 14,7 | M6 | 0,4-4,0 |
| IBM 6047 | 12,8 | 18,8 | 12,7 | 4,8 | 16,3 | M6 | 0,8-4,8 |
| IBM 6116 | 12,8 | 16,1 | 12,7 | 1,3 | 25,4 | M6 | 6,4-11,6 |
| IBM 8047 | 15,9 | 22,2 | 15,8 | 3,2 | 15,2 | M8 | 0,4-4,0 |