


### Product Group JTE/PP

Adjustable feet made of PP with stainless steel cover and hexagonal adjusting screw, swivel base




#### Standard Colours

- black RAL 9005

#### Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Cover: Stainless Steel
- Base: Polypropylene (PP)



#### Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

#### Product options on inquiry

- Further thread lengths/sizes
- Hexagon socket in thread end (please look at JTE/PP ISK)
- Plastic base in special colours according to RAL-System

D	F max.	H	H1	M	WAF	16	20	30	40	50	60	70	80	90	100	120
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
30	400	10	17	M8	13	x	x	x	x	x	x	x	x	x	x	x
30	550	10	18	M10	17	x	x	x	x	x	x	x	x	x	x	x
58	550	19,5	27	M10	17	x	x	x	x	x	x	x	x	x	x	x
58	650	19,5	29	M12	19			x	x	x	x	x	x	x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> JTE/PP 30 M10x 50