


### Product Group JTE/PP ISK

Adjustable feet made of PP with stainless steel cover and hexagonal adjusting screw with hexagon in thread end , swivel base




#### Standard Colours

- black RAL 9005

#### Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Cover: Stainless Steel
- Base: Polypropylene (PP)



#### Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

#### Product options on inquiry

- Further thread lengths/sizes
- Plastic base in special colours according to RAL-System

D	F max.	H	H1	M	WAF	SW1	20	30	40	50	60	70	80	90	100
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
30	400	10	17	M8	13	4	x	x	x	x	x	x	x	x	x
30	550	10	18	M10	17	5	x	x	x	x	x	x	x	x	x
58	550	19,5	27	M10	17	5	x	x	x	x	x	x	x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> JTE/PP ISK 30 M10x 60