


Product Group MFPA

Articulated machine feet made of glass fibre reinforced polyamide with zinced steel thread, and antislip pad at (A)





Standard Colours

- black

Material

- Thread: zinc-plated steel
- Base: glass fibre reinforced polyamide (PA-GF)
- Antislip pad: NBR 70 Shore



Product information

- Depending on the size of the thread or the foot diameter, the machine foot is provided with a chamfer on both sides or with a hexagon as a spanner flat.
- The machine foot can compensate for uneven floors up to 30°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Packaging industry, conveyor systems, automation industry, office desks, aluminium profiles

Product options on inquiry

- Delivery with additional steel nut possible.

D	F max.	H	H1	M	WAF	25	50	75	100	125	150	175	200
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm
40	1000	16,5	27	M8	12	x	x	x	x				
40	1000	16,5	27	M10	12	x	x	x	x	x			
40	1000	16,5	27	M12	12	x	x	x	x	x			
50	1100	20	30	M10	14	x	x	x	x	x			
50	1100	20	30	M12	14	x	x	x	x	x			
50	1100	20	30	M14	14	x	x	x	x	x			
65	1100	23	33	M10	14		x	x	x	x			
65	1100	23	33	M12	14		x	x	x	x			
65	1500	23	33	M14	14		x	x	x	x	x		
65	1500	23	33	M16	16		x	x	x	x	x	x	
65	1500	23	37	M20	17			x	x	x	x	x	x

Ordering example

- Group + D + M + Thread Length ----> MFPA 40 M 8x 25 (A)