


Product Group MFAF

Machine feet made of stainless steel with vibration-damping rubber base




Standard Colours

- black

Material

- Base body: AISI 304 (A2)
- Rubber: NBR 80 Shore



Product information

- Included in the scope of delivery: 2 nuts, 1 washer, 1 tooth lock washer
- The rubber of the machine base is 10 mm thick and the surface is infused with circular veins for optimum vibration damping.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The machine foot is adjusted via the square on the threaded head.
- Machine tools, injection moulding units, shearing machines, vibrators, printing machines, etc. ...

Product options on inquiry

- For higher loads, a vibration-damping plate made of NBR with a hardness of 90 Shore can be supplied.

| Order Number | D | F max. | F min. | H | L | M | WAF |
|--------------|-----|--------|--------|----|-----|-----|-----|
| | mm | kg | kg | mm | mm | | mm |
| MFAF 84 | 84 | 600 | 300 | 30 | 83 | M12 | 8 |
| MFAF 104 | 104 | 1100 | 600 | 34 | 121 | M14 | 9 |
| MFAF 120 | 120 | 1300 | 700 | 37 | 125 | M16 | 10 |
| MFAF 140 | 140 | 1600 | 800 | 45 | 128 | M16 | 10 |
| MFAF 160 | 160 | 2500 | 1200 | 45 | 135 | M20 | 13 |
| MFAF 180 | 180 | 3500 | 1700 | 45 | 135 | M20 | 13 |