



### Product Group MFAR

Machine feet made of galvanised steel with vulcanised, vibration-damping rubber pad



#### Material

- Thread: zinc-plated steel
- Jacket: zinc-plated steel
- Rubber: NBR 80 Shore, vulcanized



#### Product information

- Included in the scope of delivery: 2 nuts, 1 washer, 1 tooth lock washer
- The rubber of the machine base is 10 mm thick and the surface is infused with circular veins for optimum vibration damping.
- The foot is made of pressed moulded sheet metal. The vulcanized rubber is firmly attached to the sheet. This prevents the penetration of bacteria and ensures a high standard of hygiene.
- The machine foot can compensate for uneven floors up to 5°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The machine foot is adjusted via the square on the threaded head.
- Machine tools, injection moulding units, shearing machines, vibrators, printing machines, etc. ...

Order Number	D	F max.	F min.	H	H1	L	M	WAF
	mm	kg	kg	mm	mm	mm		mm
MFAR 80 / M12x75	80	450	250	28	25	75	M12	8
MFAR 80 / M14x100	80	450	250	28	25	100	M14	9
MFAR 100 / M12x75	100	900	500	31	28	75	M12	8
MFAR 100 / M14x100	100	900	500	31	28	125	M14	9
MFAR 100 / M16x100	100	900	500	31	28	125	M16	10
MFAR 120 / M16x125	120	1100	600	35	32	125	M16	10
MFAR 120 / M20x125	120	1100	600	35	32	125	M20	13
MFAR 120 / M24x125	120	1100	600	35	32	125	M24	16