


Product Group MFEP

Articulated machine feet made of glass fibre reinforced polyamide, stainless steel thread and vibration-damping rubber base




Standard Colours

- black

Material

- Thread: AISI 304 (A2)
- Base: glass fibre reinforced polyamide (PA-GF)
- Rubber: NBR 70 Shore



Product information

- A thicker rubber plate absorbs oscillations and vibrations.
- Depending on the size of the thread or the foot diameter, the machine foot is provided with a chamfer on both sides or with a hexagon as a spanner flat.
- The machine foot can compensate for uneven floors up to 4°.
- There are two prepared screw-on holes (closed).
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Compressors, feeders, vibrators, cleaning machines
- The foot is used in work areas with low stress.
- The vulcanised polyamide base is used to solve vibration problems.

The base is made of vulcanised polyamide and is used to solve vibration problems.

Product options on inquiry

- Thread made of stainless steel AISI 316 (A4)
- Delivery with additional steel nut possible.

A	D	d	F max.	H	H1	H2	M	WAF	50	75	100	125	150	175	200	225	250
mm	mm	mm	kg	mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
56	83	8,5	2000	28	36	10	M14	13	x	x	x	x	x	x			
56	83	8,5	2000	28	40	10	M16	13	x	x	x	x	x	x	x		
56	83	8,5	2000	28	40	10	M20	17		x	x	x	x	x	x	x	
73	103	12,5	3500	33	45	10	M16	17	x	x	x	x	x	x	x	x	x
73	103	12,5	3500	33	45	10	M20	17		x	x	x	x	x	x	x	x
73	103	12,5	3500	33	47	10	M24	20		x	x	x	x	x	x	x	x
87	123	12,5	4500	37	50	10	M16	20	x	x	x	x	x	x	x	x	x
87	123	12,5	4500	37	50	10	M20	20		x	x	x	x	x	x	x	x
87	123	12,5	4500	37	50	10	M24	20		x	x	x	x	x	x	x	x
87	123	12,5	4500	37	50	10	M30	26			x	x	x	x	x	x	x

Ordering example

- Group + D + M + Thread Length ---> MFEP 83 M14x 50