


Product Group MFSA

Machine feet made of painted steel base with zinc-plated steel screw and antislip pad (A)




Standard Colours

- daffodil yellow RAL 1007

Material

- Thread: zinc-plated steel
- Base: painted steel
- Antislip pad: NBR 70 Shore



Product information

- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Especially for large machine construction

Product options on inquiry

- Delivery with additional steel nut possible.

| D | F max. | H | H1 | M | WAF | 100 | 150 | 200 | 225 |
|-----|--------|----|----|-----|-----|-----|-----|-----|-----|
| mm | kg | mm | mm | | mm | mm | mm | mm | mm |
| 80 | 3000 | 19 | 33 | M16 | 24 | x | x | x | |
| 80 | 3500 | 19 | 33 | M20 | 24 | x | x | x | x |
| 80 | 4000 | 19 | 33 | M24 | 24 | x | x | x | x |
| 100 | 4000 | 20 | 34 | M20 | 24 | x | x | x | x |
| 100 | 4500 | 20 | 34 | M24 | 24 | x | x | x | x |
| 100 | 5000 | 20 | 34 | M30 | 30 | x | x | x | x |
| 120 | 4500 | 22 | 36 | M20 | 24 | x | x | x | x |
| 120 | 5000 | 22 | 36 | M24 | 24 | x | x | x | x |
| 120 | 6000 | 22 | 38 | M30 | 30 | x | x | x | x |
| 159 | 5000 | 23 | 36 | M20 | 24 | x | x | x | x |
| 159 | 6000 | 23 | 36 | M24 | 24 | x | x | x | x |
| 159 | 7000 | 23 | 38 | M30 | 30 | x | x | x | x |

Ordering example

- Group + D + M + Thread Length ---> MFSA 80 M16x 100 (A)