



Product Group MFSG

Machine feet made of zinc-plated steel, with 2 fixing holes and antislip-pad (A)



Material

- Base body: zinc-plated steel
- Antislip pad: NBR 70 Shore



Product information

- The antislip pad is supplied without holes.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Especially for large machine construction

Product options on inquiry

- Delivery with additional steel nut possible.

| A | D | d | F max. | H | H1 | M | WAF | 100 | 150 | 200 | 250 |
|-----|-----|------|--------|----|----|-----|-----|-----|-----|-----|-----|
| mm | mm | mm | kg | mm | mm | | mm | mm | mm | mm | mm |
| 74 | 100 | 12,5 | 3500 | 20 | 29 | M16 | 24 | x | x | x | |
| 74 | 100 | 12,5 | 4000 | 20 | 29 | M20 | 24 | x | x | x | x |
| 74 | 100 | 12,5 | 4500 | 20 | 29 | M24 | 24 | x | x | x | x |
| 90 | 120 | 12,5 | 4500 | 22 | 31 | M20 | 24 | x | x | x | x |
| 90 | 120 | 12,5 | 5000 | 22 | 31 | M24 | 24 | x | x | x | x |
| 90 | 120 | 12,5 | 6000 | 22 | 31 | M30 | 30 | x | x | x | x |
| 122 | 159 | 12,5 | 5000 | 23 | 32 | M20 | 24 | x | x | x | x |
| 122 | 159 | 12,5 | 6000 | 23 | 32 | M24 | 24 | x | x | x | x |
| 122 | 159 | 12,5 | 7000 | 23 | 32 | M30 | 30 | x | x | x | x |

Ordering example

- Group + D + M + Thread Length ----> MFSG 100 M16x 100 (A)