




### Product Group MFSSA

Articulated machine feet made of stainless steel and antislip pad (A)



#### Material

- Base body: AISI 304 (A2)
- Antislip pad: NBR 70 Shore



#### Product information

- Depending on the size of the thread or the foot diameter, the machine foot is provided with a chamfer on both sides or with a hexagon as a spanner flat.
- The machine foot can compensate for uneven floors up to 30°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

#### Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)
- Delivery with additional steel nut possible.

| D   | F max. | H    | H1   | M   | WAF | 25 | 50 | 75 | 100 | 125 | 150 | 175 | 200 | 225 | 250 |
|-----|--------|------|------|-----|-----|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| mm  | kg     | mm   | mm   |     | mm  | mm | mm | mm | mm  | mm  | mm  | mm  | mm  | mm  | mm  |
| 40  | 1000   | 14,5 | 25   | M8  | 12  | x  | x  | x  | x   |     |     |     |     |     |     |
| 40  | 1000   | 14,5 | 25   | M10 | 12  | x  | x  | x  | x   | x   |     |     |     |     |     |
| 50  | 1500   | 16   | 28   | M10 | 14  | x  | x  | x  | x   | x   |     |     |     |     |     |
| 50  | 1500   | 16   | 28   | M12 | 14  | x  | x  | x  | x   | x   |     |     |     |     |     |
| 50  | 1500   | 16   | 28   | M14 | 14  | x  | x  | x  | x   | x   |     |     |     |     |     |
| 65  | 2000   | 17   | 30   | M14 | 14  |    | x  | x  | x   | x   | x   |     |     |     |     |
| 65  | 2000   | 17   | 34,5 | M16 | 13  |    | x  | x  | x   | x   | x   | x   |     |     |     |
| 80  | 3000   | 19,5 | 36   | M16 | 13  |    | x  | x  | x   | x   | x   | x   | x   |     |     |
| 80  | 3000   | 19,5 | 36   | M20 | 17  |    |    | x  | x   | x   | x   | x   | x   | x   |     |
| 100 | 3500   | 20   | 43   | M16 | 20  |    | x  | x  | x   | x   | x   | x   | x   |     |     |
| 100 | 4500   | 20   | 43   | M20 | 20  |    |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 100 | 5500   | 20   | 44   | M24 | 20  |    |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 120 | 3500   | 23   | 46   | M16 | 20  |    | x  | x  | x   | x   | x   | x   |     |     |     |
| 120 | 4500   | 23   | 46   | M20 | 20  |    |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 120 | 5500   | 23   | 47   | M24 | 20  |    |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 120 | 6500   | 23   | 47   | M30 | 26  |    |    |    | x   | x   | x   | x   | x   | x   | x   |
| 140 | 5000   | 26   | 49   | M20 | 20  |    |    | x  | x   | x   | x   | x   |     |     |     |
| 140 | 6000   | 26   | 49   | M24 | 20  |    |    | x  | x   | x   | x   | x   |     |     |     |
| 140 | 7000   | 26   | 49   | M30 | 26  |    |    |    | x   | x   | x   | x   | x   | x   | x   |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

## Ordering example

• Group + D + M + Thread Length ---> MFSSA 40 M8x 25 (A)