



### Product Group MFSSC

Machine feet made of stainless steel



#### Material

- AISI 304 (A2)



#### Product information

- The thread is screwed into the foot and can be turned!
- The machine foot can compensate for uneven floors up to 5°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

#### Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)
- Delivery with additional steel nut possible.

| Order Number       | D  | F max. | H  | H1 | L   | M   | WAF |
|--------------------|----|--------|----|----|-----|-----|-----|
|                    | mm | kg     | mm | mm | mm  |     | mm  |
| MFSSC 30 / M8x25   | 30 | 800    | 8  | 14 | 25  | M8  | 14  |
| MFSSC 30 / M8x50   | 30 | 800    | 8  | 14 | 50  | M8  | 14  |
| MFSSC 30 / M10x25  | 30 | 800    | 8  | 14 | 25  | M10 | 14  |
| MFSSC 30 / M10x50  | 30 | 800    | 8  | 14 | 50  | M10 | 14  |
| MFSSC 30 / M10x75  | 30 | 800    | 8  | 14 | 75  | M10 | 14  |
| MFSSC 38 / M8x25   | 38 | 900    | 8  | 14 | 25  | M8  | 14  |
| MFSSC 38 / M8x50   | 38 | 900    | 8  | 14 | 50  | M8  | 14  |
| MFSSC 38 / M10x25  | 38 | 900    | 8  | 14 | 25  | M10 | 14  |
| MFSSC 38 / M10x50  | 38 | 900    | 8  | 14 | 50  | M10 | 14  |
| MFSSC 38 / M10x75  | 38 | 900    | 8  | 14 | 75  | M10 | 14  |
| MFSSC 38 / M12x50  | 38 | 900    | 8  | 14 | 50  | M12 | 14  |
| MFSSC 38 / M12x100 | 38 | 900    | 8  | 14 | 100 | M12 | 14  |

#### Ordering example

- Group + D + M + Thread Length ---> MFSSC 30 M8x 25