



Product Group MFSSF

Machine feet made of stainless steel with antislip pad



Material

- Base body: AISI 304 (A2)
- Antislip pad: NBR 70 Shore



- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Especially for large machine construction

Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)
- Delivery with additional steel nut possible.

| D | F max. | H | H1 | M | WAF | 100 | 150 | 200 | 225 | 250 |
|-----|--------|----|------|-----|-----|-----|-----|-----|-----|-----|
| mm | kg | mm | mm | | mm | mm | mm | mm | mm | mm |
| 80 | 3000 | 22 | 34,5 | M16 | 17 | x | x | x | | |
| 80 | 3500 | 22 | 34,5 | M20 | 20 | x | x | x | x | |
| 80 | 4000 | 22 | 36 | M24 | 20 | x | x | x | x | |
| 100 | 4000 | 23 | 36 | M16 | 20 | x | x | x | | |
| 100 | 4500 | 23 | 36 | M20 | 20 | x | x | x | | x |
| 100 | 5000 | 23 | 37 | M24 | 20 | x | x | x | | x |
| 120 | 4500 | 23 | 36 | M20 | 20 | x | x | x | | x |
| 120 | 5000 | 23 | 36 | M24 | 20 | x | x | x | | x |
| 120 | 6000 | 23 | 37 | M30 | 26 | x | x | x | | x |
| 159 | 5000 | 26 | 39 | M20 | 20 | x | x | x | | x |
| 159 | 6000 | 26 | 39 | M24 | 20 | x | x | x | | x |
| 159 | 7000 | 26 | 40 | M30 | 26 | x | x | x | | x |

Ordering example

- Group + D + M + Thread Length ---> MFSSF 80 M16x 100 A