


Product Group VJG

Adjusting plugs made of PA 6 for square tubes with anti-slip plug, one-piece outer body and injection moulded thread





Standard Colours

- black RAL 9005

Material

- Polyamide 6 (PA 6)
- Anti-slip insert: Polyurethane (PUR)



• The feet must be adjusted in an unloaded state. • The specified axial, static load capacity refers to a screw turned out 10 mm and resting on the full surface. • Adjusting plugs are not suitable as load gliders. • Adjusting plugs are not suitable for dynamic load.

• *) = The lamella shape of the nut can be closed or interrupted

• ***) = from Ø 60 mm supplied with mounted threaded shell

• Please observe the material hints for polyamide (PA).

Product options on inquiry

- Further sizes
- Other special productions

| Order Number | A | F max. | H | H1 | L | L1 | M | WAF | t |
|----------------------------------|----|--------|----|----|------|------|-------|-----|-------|
| | mm | kg | mm | mm | mm | mm | | mm | mm |
| VJG 25x25x1-1,5 /M16x25 /8k | 25 | 150 | 5 | 5 | 20 | 22,5 | M16 | 24 | 1-1,5 |
| VJG 25x25x1,5-2 /M16x25 /8k | 25 | 150 | 5 | 5 | 20 | 22,5 | M16 | 24 | 1,5-2 |
| VJG 30x30x1-1,5 /M22x25 /8k | 30 | 300 | 5 | 5 | 19,5 | 29 | M22 | 28 | 1-1,5 |
| VJG 30x30x1,5-2 /M22x25 /8k * | 30 | 300 | 5 | 5 | 19,5 | 29 | M22 | 28 | 1,5-2 |
| VJG 35x35x1,5-2 /M22x25 /8k | 35 | 300 | 5 | 5 | 29,3 | 29 | M22 | 28 | 1,5-2 |
| VJG 35x35x2-2,5 /M22x25 /8k | 35 | 300 | 5 | 5 | 29,3 | 29 | M22 | 28 | 2-2,5 |
| VJG 40x40x1,5-2 /M22x25 /8k | 40 | 300 | 5 | 5 | 29,3 | 29 | M22 | 28 | 1,5-2 |
| VJG 40x40x2-2,5 /M22x25 /8k | 40 | 300 | 5 | 5 | 29,3 | 29 | M22 | 28 | 2-2,5 |
| VJG 45x45x1,5-2 /M30x30 /8k | 45 | 300 | 5 | 5 | 29,3 | 31 | M30 | 41 | 1,5-2 |
| VJG 50x50x1,5-2 /M30x30 /8k | 50 | 300 | 5 | 5 | 29,3 | 31 | M30 | 41 | 1,5-2 |
| VJG 50x50x2-2,5 /M30x30/8k | 50 | 300 | 5 | 5 | 29,3 | 31 | M30 | 41 | 2-2,5 |
| VJG 60x60x1,5-2/S42x2x40/12k *** | 60 | 175 | 6 | 10 | 34,8 | 37 | M42x2 | 58 | 1,5-2 |